## NSN 6680-00-580-4495

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-580-4495 **Overall Length:** 22.750 inches Media For Which Designed: Air **Inlet Connection Type:** Hose nipple **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Glass **Unit Type:** Mounted **Scale Quantity: Outlet Connection Type:** Threaded Scale Marking: Cfm Scale Type: Direct capacity reading or millimeter reference reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Dial Scale Marking Range:** +10.0/+260.0 **Outlet Connection Size:** 2-1/4 - 12 un - 3b Float Type: Guided Float Material: Uscolite **Guide Type:** Solid rod **Integral Heat Source:** 

Not included

**Maximum Working Pressure:** 

65.0 pounds per square inch

## NSN 6680-00-580-4495

Flow Rate Indicating Meter - Page 2 of 2



Inlet Connection Size:
2.875 in. Diameter hose nipple
Metering Tube Quantity:
1
Maximum Air Capacity In Cubic Feet Per Minute:
260.0
Dial Scale Smallest Increment:
10cfm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t