

View Online at <https://aerobasegroup.com/nsn/6680-00-585-4134>

Spline Major Diameter:

0.3757 inches first end

Overall Length:

24.938 inches

Flange Thickness:

0.200 inches first end

Spline Quantity:

14 first end

Spline Minor Diameter:

0.325 inches first end

Tip Length:

1.000 inches first end

Shank Outside Diameter:

0.655 inches second end

Pitch Diameter:

0.350 inches first end

Shoulder Outside Diameter:

0.680 inches first end

Core Material:

Steel

Core Diameter:

0.313 inches

End Type:

Round, external splined first end

End Connection Type:

Mounting flange first end

Spline Pressure Angle In Deg:

30.0 first end

Spline Length:

0.660 inches first end

Spline Type:

Straight first end

Setscrew:

Not included first end

Casing Material:

Bronze

Cross Section Size And Location:

0.535 inches diameter first end

Torsional Deflection Rating:

12 degrees ft of shaft at 15 lb/in. Load winding direction and 10 degrees per ft of shaft at 15 lb/in. Load unwinding direction

Casing Length Between Ferrules:

12.750 inches

Casing Outside Diameter:

0.719 inches

Casing Protective Device Type:

Rubber cover

Swivel End:

Not provided second end

Enddiameter:

0.910 inches first end

Lubrication Fitting:

Not provided second end

Corelength:

15.984 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Removable

Minimum Operating Radius:

10.000 inches

Fsc Application Data:

Radarw set, nonairborne, except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e