## NSN 6680-00-624-8767

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-624-8767

Thread Class:
2b second end
Thread Direction:
Right-hand both ends
Overall Length:
Between 114.969 inches and 115.063 inches
Thread Depth:
0.219 inches first end
Tip Length:
0.563 inches and 0.625 inches first end
Core Material:
Steel
Screw Thread Series Designator:
Uns first end
Core Diameter:
0.130 inches
Thread Location:
Internal both ends
End Type:
Square male second end
End Connection Type:
Threaded internal both ends
Setscrew:
Not included both ends
Casing Material:
Steel
Cross Section Size And Location:
0.201 inches diameter and 0.205 inches diameter first end
Casing Surface Treatment:
Zinc coated
Casing Length Between Ferrules:
114.000 inches
Casing Outside Diameter:
Between 0.2405 inches and 0.2455 inches
Swivel End:
Not provided both ends
Enddiameter:
0.938 inches first end
Overall End Size:
Second end: 0.312 in. Deep slot
Lubrication Fitting:
Not provided both ends

## NSN 6680-00-624-8767

Flexible Shaft Assembly - Page 2 of 2



Corelength:

Between 114.969 inches and 115.063 inches

**Core Rotation Direction:** 

Clockwise

Core Removability:

Removable

**Special Features:** 

Counterclockwise core rotation direction

**Fsc Application Data:** 

Speedometer drive, combat vehicle

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

T246-e