NSN 6680-00-624-8767

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-624-8767

| Thread Class: |
|---|
| 2b second end |
| Thread Direction: |
| Right-hand both ends |
| Overall Length: |
| Between 114.969 inches and 115.063 inches |
| Thread Depth: |
| 0.219 inches first end |
| Tip Length: |
| 0.563 inches and 0.625 inches first end |
| Core Material: |
| Steel |
| Screw Thread Series Designator: |
| Uns first end |
| Core Diameter: |
| 0.130 inches |
| Thread Location: |
| Internal both ends |
| End Type: |
| Square male second end |
| End Connection Type: |
| Threaded internal both ends |
| Setscrew: |
| Not included both ends |
| Casing Material: |
| Steel |
| Cross Section Size And Location: |
| 0.201 inches diameter and 0.205 inches diameter first end |
| Casing Surface Treatment: |
| Zinc coated |
| Casing Length Between Ferrules: |
| 114.000 inches |
| Casing Outside Diameter: |
| Between 0.2405 inches and 0.2455 inches |
| Swivel End: |
| Not provided both ends |
| Enddiameter: |
| 0.938 inches first end |
| Overall End Size: |
| Second end: 0.312 in. Deep slot |
| Lubrication Fitting: |
| Not provided both ends |

NSN 6680-00-624-8767

Flexible Shaft Assembly - Page 2 of 2



| Corelength: |
|---|
| Between 114.969 inches and 115.063 inches |
| Core Rotation Direction: |
| Clockwise |
| Core Removability: |
| Removable |
| Special Features: |
| Counterclockwise core rotation direction |
| Fsc Application Data: |
| Speedometer drive, combat vehicle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: T246-e