

View Online at <https://aerobasegroup.com/nsn/6680-00-628-0717>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Overall Length:

Between 68.313 inches and 68.375 inches

Wrenching Facility Outside Diameter:

0.750 inches second end

Thread Depth:

0.188 inches both ends

Tip Length:

0.875 inches and 1.125 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Zinc coated

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Square male second end

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.201 inches diameter and 0.205 inches diameter first end

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

Between 66.875 inches and 67.000 inches

Casing Outside Diameter:

0.500 inches

Casing Protective Device Type:

Rubber cover

Swivel End:

Not provided first end

Enddiameter:

1.125 inches first end

Lubrication Fitting:

Not provided both ends

Corelength:

Between 68.281 inches and 68.344 inches

Core Rotation Direction:

Clockwise

Core Removability:

Nonremovable

Special Features:

Counterclockwise core rotation direction

Fsc Application Data:

Tachometer drive, vehicular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e