NSN 6680-00-679-4635

Wrenching Facility Outside Diameter:

0.875 inches both ends

Thread Depth:

Thread Class:
2b second end
Thread Direction:
Right-hand both ends
Overall Length:
104.000 inches

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-679-4635

| 0.250 inches both end | , | |
|-------------------------|--------------|--|
| Tip Length: | | |
| 0.500 inches both end | i | |
| Core Material: | | |
| Steel | | |
| Screw Thread Series | esignator: | |
| Uns both ends | | |
| Core Surface Treatme | nt: | |
| Cadmium plated | | |
| Core Diameter: | | |
| 0.130 inches | | |
| Thread Location: | | |
| Internal both ends | | |
| End Type: | | |
| Round keyed both end | | |
| End Connection Type | | |
| Threaded internal both | ends | |
| Setscrew: | | |
| Not included both ends | | |
| Casing Material: | | |
| Steel | | |
| Wrenching Facility Ty | pe: | |
| Knurled surface both e | ds | |
| Cross Section Size A | d Location: | |
| 0.104 inches across fla | ts both ends | |
| Casing Surface Treat | nent: | |
| Zinc coated | | |
| Casing Length Betwe | n Ferrules: | |
| 103.000 inches | | |
| Casing Outside Diam | ter: | |
| 0.243 inches | | |
| Swivel End: | | |
| Not provided both ends | | |

NSN 6680-00-679-4635

Flexible Shaft Assembly - Page 2 of 2



| Enddiameter: |
|--|
| 1.000 inches both ends |
| Lubrication Fitting: |
| Not provided both ends |
| Corelength: |
| 104.000 inches |
| Core Rotation Direction: |
| Clockwise |
| Core Removability: |
| Removable |
| Minimum Operating Radius: |
| 3.000 inches |
| Special Features: |
| Counterclockwise core rotation direction |
| Fsc Application Data: |
| Tachometer, mechanical, fixed mounting |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T246-e |
| |