

View Online at <https://aerobasegroup.com/nsn/6680-00-684-5418>

Thread Class:

2b second end

Thread Direction:

Right-hand both ends

Thread Length:

0.3125 inches both ends

Overall Length:

138.743125 inches

Tip Length:

0.734 inches both ends

Shank Outside Diameter:

0.9375 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Surface Treatment:

Zinc

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Round keyed both ends

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Cross Section Size And Location:

0.152 inches diameter both ends

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

138.000 inches

Casing Outside Diameter:

0.4375 inches

Casing Protective Device Type:

Coiled spring protector

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

138.734375 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

3.500 inches

Special Features:

Counterclockwise core rotation direction

Fsc Application Data:

Speedometer, mechanical motion measuring instrument

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e