NSN 6680-00-688-7650

Rotating Counter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-688-7650

Overall Length: 1.695 inches Overall Height: 1.495 inches Overall Width: 0.924 inches Shaft Diameter: 0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Overall Height: 1.495 inches Overall Width: 0.924 inches Shaft Diameter: 0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
1.495 inches Overall Width: 0.924 inches Shaft Diameter: 0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Overall Width: 0.924 inches Shaft Diameter: 0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Shaft Diameter: 0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Shaft Diameter: 0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
0.090 inches Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Shaft Length: 0.297 inches Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Congest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Longest Horizontal Distance Between Mounting Centers: 0.757 inches Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Shortest Horizontal Distance Between Mounting Centers: 0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
0.618 inches Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Longest Vertical Distance Between Mounting Centers: 0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
0.709 inches Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Register Quantity: 1 Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Figure Quantity Per Register: 4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
4 single register single tier Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Figure Height: 0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
0.187 inches single register single tier Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
Shaft Revolutions Per Count: 1.00 single register single tier Maximum Count Rate: 1200.0 per minute single register single tier
1.00 single register single tierMaximum Count Rate:1200.0 per minute single register single tier
Maximum Count Rate: 1200.0 per minute single register single tier
1200.0 per minute single register single tier
Mounting Arrangement Style:
Three position triangular offset
Register Reset Method:
Total counter manual single register single tier
Register Function:
Add single register single tier and subtract single register single tier
Add single register single tier and subtract single register single tier Actuating Device Location:
Actuating Device Location:
Actuating Device Location: Left side single register single tier
Actuating Device Location: Left side single register single tier Mounting Facility Type And Quantity:
Actuating Device Location: Left side single register single tier Mounting Facility Type And Quantity: 2 slot and 1 unthreaded hole
Actuating Device Location: Left side single register single tier Mounting Facility Type And Quantity: 2 slot and 1 unthreaded hole Mounting Type For Which Designed:

Numeral Readout:

0000 single register single tier and 8959 single register single tier

NSN 6680-00-688-7650

Rotating Counter - Page 2 of 2



Shaft Rotation Direction And Maximum Speed In Rpm:

1200.0 clockwise single register single tier and 1200.0 counterclockwise single register single tier

Special Features:

Counter has fifth drum with letters n and s

Color:

White single register single tier figure

Style Designator:

Square/rectangular cased

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A236a0