NSN 6680-00-725-3332

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-725-3332 **Overall Length:** 23.500 inches Media For Which Designed: Hydraulic oil **Inlet Connection Type:** Threaded **End Application:** Poseidon **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gal per min Scale Type: Direct capacity reading Float Quantity: **Tube Material: Dial Scale Marking Range:**

Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included +3.0/+30.0 **Outlet Connection Size:** 1.875 in. Un Base: Not included Float Type: Guided

NSN 6680-00-725-3332

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel
Guide Type:
Solid rod
Integral Heat Source:
Not included
Maximum Working Pressure:
300.0 pounds per square inch
Inlet Connection Size:
1.875 in. Un
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.5 gal
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Swivel
Alarm Signal:
Not included
Special Features:
Plastic protective shield
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T13/Lt