NSN 6680-00-731-5960

2

Rate Of Flow Transmitter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-731-5960

Terminal Quantity:

Terminal Type:
Socket
Overall Length:
3.880 inches
Overall Width:
1.630 inches
Current Type:
Ac
Frequency Rating:
Between 0.12 kilohertz and 1.20 kilohertz
Attachment Feature Quantity:
2
Overall Thickness:
5.000 inches
Actuation Method:
Pivoted vane
Voltage Rating:
Between 0.084 volts and 0.810 volts
Electrical Connection Quantity:
1
Electrical Connection Controlling Agency:
Ms
Electrical Connection Identifying Number:
Ms3106a10sl4s
Mechanical Connection Quantity:
2
Mechanical Connection Size:
1.0 in. Dia
Mechanical Connection Type:
Male threaded tube
Mounting Method:
Thd male tube connections
Measurement Range:
+1140.0/+22800.0 pounds per hour
Phase:
Single
Fsc Application Data:
Transmitter, rate of flow, except engine

Reference Number Differentiating Characteristics:

As differentiated by measurement range, calibrated for 1523.4 cycles per gal, calibrated for 4794.8 pph at 120 cps, calibrated for 17948 pph at 1200 cps

NSN 6680-00-731-5960

Rate Of Flow Transmitter - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T145-b