

View Online at <https://aerobasegroup.com/nsn/6680-00-737-3846>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Overall Length:

Between 115.375 inches and 115.813 inches

Wrenching Facility Outside Diameter:

0.750 inches second end

Thread Depth:

0.188 inches both ends

Tip Length:

1.375 inches and 1.425 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Zinc coated

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Square male second end

End Connection Type:

Threaded internal both ends

Spline Type:

Involute second end

Setscrew:

Not included both ends

Casing Material:

Plastic and steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.201 inches diameter and 0.205 inches diameter first end

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

Between 113.875 inches and 114.000 inches

Casing Outside Diameter:

0.500 inches

Casing Protective Device Type:

Rubber cover

Swivel End:

Not provided both ends

Enddiameter:

1.125 inches first end

Lubrication Fitting:

Not provided both ends

Corelength:

Between 115.719 inches and 115.781 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Special Features:

Counterclockwise core rotation direction

Fsc Application Data:

Speedometer drive, vehicular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e