## NSN 6680-00-737-4077

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-737-4077

Inread Class:
2b first end
Thread Direction:
Right-hand both ends
Overall Length:
Between 86.750 inches and 86.875 inches
Thread Depth:
0.875 inches second end
Tip Length:
0.625 inches first end
Core Material:
Steel
Screw Thread Series Designator:
Uns first end
Core Surface Treatment:
Cadmium plated
Core Diameter:
0.130 inches
Thread Location:
Internal first end
End Type:
Square male second end
End Connection Type:
Threaded internal first end
Setscrew:
Not included both ends
Casing Material:
Steel
Cross Section Size And Location:
0.203 inches diameter first end
Casing Surface Treatment:
Cadmium plated finish
Casing Length Between Ferrules:
Between 85.875 inches and 86.000 inches
Casing Outside Diameter:
0.297 inches
Swivel End:
Not provided both ends
Enddiameter:
1.125 inches first end

**Lubrication Fitting:**Not provided both ends

## NSN 6680-00-737-4077

Flexible Shaft Assembly - Page 2 of 2



Corelength:
Between 86.750 inches and 86.875 inches
Core Rotation Direction:
Clockwise
Core Removability:
Nonremovable
Special Features:
Counterclockwise core rotation direction
Fsc Application Data:
Speedometer drive, combat vehicle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e