NSN 6680-00-740-9701



Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-740-9701 **Thread Class:** 2b both ends **Thread Direction:** Right-hand both ends **Overall Length:** Between 88.473 inches and 88.777 inches **Thread Depth:** 0.327 inches first end Tip Length: 0.950 inches and 1.010 inches second end **Core Material:** Steel **Screw Thread Series Designator:** Uns first end **Core Diameter:** Between 0.128 inches and 0.152 inches **Thread Location:** Internal both ends End Type: Square male second end Width Across Flats: 1.000 inches first end **End Connection Type:** Threaded internal both ends Setscrew:

Not included both ends

Casing Material:

Rubber

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.150 inches diameter and 0.153 inches diameter first end

Machined Feature Size:

0.261 in. Min Ig by 0.057 to 0.060 in. W drive key

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

Between 87.438 inches and 87.562 inches

Casing Outside Diameter:

Between 0.300 inches and 0.500 inches

Casing Protective Device Type:

Plastic cover or rubber cover

NSN 6680-00-740-9701Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
1.188 inches first end
Lubrication Fitting:
Not provided both ends
Corelength:
Between 88.473 inches and 88.777 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
5.000 inches
Special Features:
Counterclockwise core rotation direction
Departure From Cited Document:
As modified by length
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e