## NSN 6680-00-764-4740

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-764-4740



**Overall Length:** 20.750 inches Media For Which Designed: Water **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Lb per min Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +1.3/+12.5 **Outlet Connection Size:** 0.500 in. Npt Base: Not included Float Type: Guided Float Material:

Steel, corrosion resisting

## NSN 6680-00-764-4740

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
300.0 pounds per square inch
Inlet Connection Size:
0.500 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.225 lb per min
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Float part no. 8rv31, tube no. R8m25-2; has valve for regulating flow rate
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t