NSN 6680-00-766-6551

Rotating Counter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-766-6551

Overall Length:
5.875 inches
Overall Height:
4.281 inches
Overall Width:
3.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.438 inches
Longest Horizontal Distance Between Mounting Centers:
3.000 inches
Shortest Horizontal Distance Between Mounting Centers:
1.500 inches
Longest Vertical Distance Between Mounting Centers:
5.375 inches
End Application:
Poseidon; itt defense communications inc, antenna, bra/6
Register Quantity:
1
Figure Quantity Per Register:
Figure Quantity Per Register: 3 single register single tier
3 single register single tier
3 single register single tier Figure Height:
3 single register single tier Figure Height: 0.125 inches single register single tier
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier Mounting Facility Type And Quantity:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier Mounting Facility Type And Quantity: 3 threaded hole
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier Mounting Facility Type And Quantity: 3 threaded hole Mounting Type For Which Designed:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier Mounting Facility Type And Quantity: 3 threaded hole Mounting Type For Which Designed: Panel rear single register single tier
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier Mounting Facility Type And Quantity: 3 threaded hole Mounting Type For Which Designed: Panel rear single register single tier Numeral Display Method:
3 single register single tier Figure Height: 0.125 inches single register single tier Shaft Revolutions Per Count: 0.10 single register single tier Mounting Arrangement Style: Three position triangular Register Function: Add single register single tier and subtract single register single tier Actuating Device Location: Front single register single tier Mounting Facility Type And Quantity: 3 threaded hole Mounting Type For Which Designed: Panel rear single register single tier Numeral Display Method: Drum

Style Designator:

Square/rectangular cased

NSN 6680-00-766-6551

Rotating Counter - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A236a0