## NSN 6680-00-766-6551

Rotating Counter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-766-6551

Overall Length:
5.875 inches
Overall Height:
4.281 inches
Overall Width:
3.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.438 inches
Longest Horizontal Distance Between Mounting Centers:
3.000 inches
<b>Shortest Horizontal Distance Between Mounting Centers:</b>
1.500 inches
Longest Vertical Distance Between Mounting Centers:
5.375 inches
End Application:
Poseidon; itt defense communications inc, antenna, bra/6
Register Quantity:
1
Figure Quantity Per Register:
Figure Quantity Per Register:  3 single register single tier
3 single register single tier
3 single register single tier  Figure Height:
3 single register single tier  Figure Height:  0.125 inches single register single tier
3 single register single tier  Figure Height:  0.125 inches single register single tier  Shaft Revolutions Per Count:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style:  Three position triangular
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style:  Three position triangular  Register Function:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style:  Three position triangular  Register Function:  Add single register single tier and subtract single register single tier
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier  Mounting Facility Type And Quantity:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier  Mounting Facility Type And Quantity: 3 threaded hole
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier  Mounting Facility Type And Quantity: 3 threaded hole  Mounting Type For Which Designed:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier  Mounting Facility Type And Quantity: 3 threaded hole  Mounting Type For Which Designed: Panel rear single register single tier
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier  Mounting Facility Type And Quantity: 3 threaded hole  Mounting Type For Which Designed: Panel rear single register single tier  Numeral Display Method:
3 single register single tier  Figure Height: 0.125 inches single register single tier  Shaft Revolutions Per Count: 0.10 single register single tier  Mounting Arrangement Style: Three position triangular  Register Function: Add single register single tier and subtract single register single tier  Actuating Device Location: Front single register single tier  Mounting Facility Type And Quantity: 3 threaded hole  Mounting Type For Which Designed: Panel rear single register single tier  Numeral Display Method:  Drum

Style Designator:

Square/rectangular cased

## NSN 6680-00-766-6551

Rotating Counter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A236a0