NSN 6680-00-791-2774

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-791-2774 **Overall Length:** 20.625 inches Media For Which Designed: Stoddard solvent **Inlet Connection Type:** Threaded Dial Range: +0.0/+150.0 **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gal per hr Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +30.0/+150.0 **Outlet Connection Size:** 3/4 in. Npt Base: Not included Float Type:

Guided

NSN 6680-00-791-2774

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel
Guide Type:
Beaded tube
Integral Heat Source:
Not included
Inlet Connection Size:
3/4 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
1 gal per hr
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Swivel
Alarm Signal:
Not included
Special Features:
Plastic safety shield; direct reading scale, 188 gph, specification grav 0.83, viscosi type 1.0 cps
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t