Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-791-2777

Overall Length: 13.375 inches Media For Which Designed: Stoddard solvent Inlet Connection Type: Threaded **Integral Relief Valve:** Not included Meter Type: Float **Design Type:** Case Unit Type: Mounted Scale Quantity: 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Cc per min Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method: Direct line**

Carrying Handle:

Not included

Dial Scale Marking Range:

+5.0 to 60.0

Outlet Connection Size:

1/4 in. Npt

Base:

Not included

Float Type:

Free

Float Material:

Sapphire

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source: Not included Maximum Working Pressure: Not rated **Inlet Connection Size:** 1/4 in. Npt Metering Tube Quantity: 1 **Dial Scale Smallest Increment:** 2 cc per min **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Swivel **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Swivel Alarm Signal: Not included **Reference Number Differentiating Characteristics:** Apsj, ateq, ackl, astw, bhby, aewh, cpzj, cpzk, awae, bjdm, cpzm, bhsq, abhp, apqb, axgy, acqw, cpzd, cpzp, cpzq, arth, bhcm, cpzr and cpzs Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: T134-t