NSN 6680-00-791-2777

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-791-2777



Overall Length: 13.375 inches Media For Which Designed: Stoddard solvent **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Cc per min Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +5.0 to 60.0 **Outlet Connection Size:** 1/4 in. Npt Base: Not included Float Type: Free

Float Material:

Sapphire

NSN 6680-00-791-2777

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source:
Not included
Maximum Working Pressure:
Not rated
Inlet Connection Size:
1/4 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
2 cc per min
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Swivel
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Apsj, ateq, ackl, astw, bhby, aewh, cpzj, cpzk, awae, bjdm, cpzm, bhsq, abhp, apqb, axgy, acqw, cpzd, cpzp, cpzq, arth, bhcm, cpzr and
cpzs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
T134-t