

View Online at <https://aerobasegroup.com/nsn/6680-00-798-3057>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Overall Length:

Between 145.078 inches and 145.391 inches

Thread Depth:

0.375 inches second end

Tip Length:

0.950 inches and 1.010 inches second end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Zinc coated

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Square male second end

Width Across Flats:

1.000 inches first end

End Connection Type:

Threaded internal both ends

Setscrew:

Not included first end

Casing Material:

Rubber and steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.150 inches diameter and 0.153 inches diameter first end

Casing Surface Treatment:

Any acceptable

Casing Length Between Ferrules:

Between 143.937 inches and 144.062 inches

Casing Outside Diameter:

Between 0.300 inches and 0.500 inches

Casing Protective Device Type:

Plastic cover or rubber cover

Swivel End:

Not provided both ends

Overall End Size:

1.188 in. W first end

Lubrication Fitting:

Not provided both ends

Corelength:

Between 145.047 inches and 145.359 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

5.000 inches

Special Features:

Counterclockwise core rotation direction.Torsion strength either direction 15.0 lbs.

Fsc Application Data:

Speedometer, self-propelled gun

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e