

View Online at <https://aerobasegroup.com/nsn/6680-00-798-7296>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Overall Length:

Between 66.078 inches and 66.391 inches

Thread Depth:

0.375 inches second end

Tip Length:

0.734 inches and 0.922 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Zinc coated

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Square male second end

Width Across Flats:

1.000 inches first end

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.150 inches diameter and 0.153 inches diameter first end

Casing Surface Treatment:

Cadmium plated

Casing Length Between Ferrules:

Between 64.937 inches and 65.063 inches

Casing Outside Diameter:

0.688 inches

Casing Protective Device Type:

Rubber cover

Swivel End:

Not provided both ends

Overall End Size:

First end: 1.188 in. W; second end: 0.875 in. W

Lubrication Fitting:

Not provided both ends

Corelength:

Between 66.047 inches and 66.359 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Special Features:

Counterclockwise core rotation direction

Fsc Application Data:

Speedometer, carrier, personnel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e