

NSN 6680-00-809-6822 Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-809-6822 **Overall Length:** 33.500 inches Media For Which Designed: Hydraulic oil **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Accessory Components And Quantity:** Tube brush, 2, float lifter, 1 **Meter Type:** Float **Design Type:** Case **Unit Type:** Portable **Scale Quantity:** 2 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading

Float Quantity:

**Tube Material:** 

Glass

**Carrying Handle:** 

Included

**Dial Scale Marking Range:** 

+5.5/+60.0

**Outlet Connection Size:** 

2 in. lps

Base:

Not included

Float Type:

Guided

Float Material:

Steel, stainless

## NSN 6680-00-809-6822

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Molded glass integral w/tube
Integral Heat Source:
Not included
Maximum Working Pressure:
75.0 pounds per square inch
Inlet Connection Size:
2 in. lps
Metering Tube Quantity:
2
Dial Scale Smallest Increment:
0.02 gpm
Dial Scale Reference Pointer:
Not included
Float Quantity Per Tube:
1
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t