

View Online at <https://aerobasegroup.com/nsn/6680-00-814-4562>

**Overall Length:**

39.430 inches

**Media For Which Designed:**

Air

**Inlet Connection Type:**

Threaded

**Integral Relief Valve:**

Included

**Meter Type:**

Float

**Design Type:**

Case

**Unit Type:**

Mounted

**Scale Quantity:**

3

**Construction:**

Inclosed w/sight window

**Outlet Connection Type:**

Threaded

**Scale Marking:**

Cfm

**Scale Type:**

Direct capacity reading

**Float Quantity:**

3

**Tube Material:**

Glass

**Mounting Method:**

Flush panel

**Carrying Handle:**

Not included

**Unit Location:**

Lower right front

**Dial Scale Marking Range:**

+0.01/+11.00

**Outlet Connection Size:**

3/4 in. Tube size

**Base:**

Not included

**Float Type:**

Guided

**Float Material:**

Steel, corrosion resisting

**Guide Type:**

Beaded tube

**Integral Heat Source:**

Not included

**Maximum Working Pressure:**

100.0 pounds per square inch

**Inlet Connection Size:**

3/4 in. Tube size

**Metering Tube Quantity:**

3

**Dial Scale Smallest Increment:**

0.0001 cfm

**Dial Scale Reference Pointer:**

Not included

**Float Quantity Per Tube:**

1

**Spinning Float:**

Not included

**Integral Pulsation Dampener:**

Not included

**Inlet Connection Position For Which Designed:**

Horizontal

**Inlet Connection Device Type:**

Stationary

**Outlet Connection Position For Which Designed:**

Horizontal

**Outlet Connection Device Type:**

Stationary

**Alarm Signal:**

Not included

**Reference Number Differentiating Characteristics:**

As differentiated by metering tube quantity, tube material, scale quantity, scale type, media for which designed, scale marking, dial scale marking range, dial scale smallest increment, unit type, inlet connection type, inlet connection size, inlet connection position for which designed, inlet connection device type, outlet connection type, outlet connection size, outlet connection position for which designed, outlet connection device type, integral relief valve, w/drip indicator, w/scale calibrated at 70 degrees f and 30 psia at inlet and 100 degrees f and 14.7 psia at discharge

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

---