

NSN 6680-00-814-8726 Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-814-8726 **Overall Length:** 33.875 inches Media For Which Designed: Calibrated fluid **Inlet Connection Type:** Threaded **Integral Relief Valve:** Included **Accessory Components And Quantity:** 1 drip indicator **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 2 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Lb per hr Scale Type: Direct capacity reading Float Quantity:

Tube Material:

Glass

Mounting Method:

Flush panel

Unit Location:

Lower right front

Dial Scale Marking Range:

+1760.0/+55000.0

Outlet Connection Size:

3 in. Tube

Float Type:

Guided

Float Material:

Steel, corrosion resisting

NSN 6680-00-814-8726

Flow Rate Indicating Meter - Page 2 of 2



| Guide Type: |
|---|
| Beaded tube |
| Integral Heat Source: |
| Not included |
| Maximum Working Pressure: |
| 100.0 pounds per square inch |
| Inlet Connection Size: |
| 3 in. Tube size |
| Metering Tube Quantity: |
| 2 |
| Dial Scale Smallest Increment: |
| 5 lb |
| Dial Scale Reference Pointer: |
| Included |
| Float Quantity Per Tube: |
| 1 |
| Spinning Float: |
| Not included |
| Integral Pulsation Dampener: |
| Not included |
| Inlet Connection Position For Which Designed: |
| Horizontal |
| Inlet Connection Device Type: |
| Stationary |
| Outlet Connection Position For Which Designed: |
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Special Features: |
| Scales calibrated for mil-f-7024, type 2, fluid at 80 degrees f |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T134-t |