

View Online at <https://aerobasegroup.com/nsn/6680-00-814-8727>

**Overall Length:**

39.430 inches

**Media For Which Designed:**

Calibration fluid

**Inlet Connection Type:**

Threaded

**Integral Relief Valve:**

Not included

**Meter Type:**

Float

**Design Type:**

Case

**Unit Type:**

Mounted

**Scale Quantity:**

2

**Construction:**

Inclosed w/sight window

**Outlet Connection Type:**

Threaded

**Scale Marking:**

Lb per hour

**Scale Type:**

Direct capacity reading

**Float Quantity:**

2

**Tube Material:**

Glass

**Mounting Method:**

Flush panel

**Carrying Handle:**

Not included

**Dial Scale Marking Range:**

+19.0/+585.0

**Outlet Connection Size:**

0.750 in. Tube size

**Base:**

Not included

**Float Type:**

Guided

**Float Material:**

Steel, corrosion resisting

**Guide Type:**

Beaded tube

**Integral Heat Source:**

Not included

**Maximum Working Pressure:**

250.0 pounds per square inch

**Inlet Connection Size:**

0.750 in. Tube size

**Metering Tube Quantity:**

2

**Dial Scale Smallest Increment:**

0.100 lb per hour

**Dial Scale Reference Pointer:**

Not included

**Float Quantity Per Tube:**

1

**Spinning Float:**

Not included

**Integral Pulsation Dampener:**

Not included

**Inlet Connection Position For Which Designed:**

Horizontal

**Inlet Connection Device Type:**

Stationary

**Outlet Connection Position For Which Designed:**

Horizontal

**Outlet Connection Device Type:**

Stationary

**Alarm Signal:**

Not included

**Reference Number Differentiating Characteristics:**

Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk, apqb, axgy, acqw, cpzd, cpzp, cpzq, acrn, acrl, acrm, arth, bhcm, cpzr, cpzs, bhcs, bhct, bhcw, w/dip indicator, w/scales calibrated for mil-f-7024a, type ii, fluid at 80 degrees f

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T134-t