NSN 6680-00-815-5516

Rate Of Flow Transmitter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-815-5516

| Terminal Quantity: |
|---|
| 4 |
| Terminal Type: |
| Pin contacts |
| Overall Length: |
| 3.880 inches |
| Overall Width: |
| 1.630 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.0 hertz |
| Attachment Feature Quantity: |
| 2 |
| Overall Thickness: |
| 3.625 inches |
| Actuation Method: |
| Pivoted vane and magnet |
| Voltage Rating: |
| 0.030 volts |
| Electrical Connection Quantity: |
| 1 |
| Electrical Connection Controlling Agency: |
| An |
| Electrical Connection Identifying Number: |
| Part no. An3102a-10sl-4p |
| Mechanical Connection Quantity: |
| 2 |
| Mechanical Connection Size: |
| 1 in. Od |
| Mechanical Connection Type: |
| Male flared tube |
| Mounting Method: |
| Thd male tube |
| Measurement Range: |
| +950.0/+22800.0 pounds per hour |
| Phase: |
| Single |
| Reference Number Differentiating Characteristics: |
| As differentiated by k factor 20 point calibration using mil-c-7024, type 2 at 80 degrees f, form 127 |
| Shelf Life: |

N/a

NSN 6680-00-815-5516

Rate Of Flow Transmitter - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

T145-b