

View Online at <https://aerobasegroup.com/nsn/6680-00-821-9471>

Thread Class:

2 both ends

Thread Direction:

Right-hand both ends

Overall Length:

18.328 inches

Wrenching Facility Outside Diameter:

0.718 inches second end

Thread Depth:

0.375 inches first end

Tip Length:

0.3848 inches both ends

Shank Outside Diameter:

0.343 inches both ends

Shoulder Outside Diameter:

0.578 inches second end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Diameter:

0.128 inches

Thread Location:

Internal both ends

End Type:

Square male both ends

End Connection Type:

Shouldered ferrule both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.070 inches diameter both ends

Torsional Deflection Rating:

15 degrees ft-lb in. Torsional deflection rating

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

5.250 inches

Casing Outside Diameter:

0.260 inches

Casing Protective Device Type:

Braided wire shield and coiled spring protector

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches first end

Lubrication Fitting:

Not provided both ends

Corelength:

18.625 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

25.000 inches

Special Features:

One end with protruding core only

Fsc Application Data:

Tachometer, mechanical, fixed mounting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e