NSN 6680-00-832-7566

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-832-7566

Thread Class: 2b second end **Thread Length:** 0.375 inches second end **Overall Length:** Between 58.578 inches and 58.891 inches Tip Length: 0.734 inches first end and 0.922 inches first end **Core Material:** Steel **Screw Thread Series Designator:** Uns first end **Core Surface Treatment:** Zinc coated **Core Diameter:** 0.150 inches **Thread Location:** Internal second end End Type: Square male second end Width Across Flats: 1.000 inches first end **End Connection Type:** Threaded internal second end Setscrew: Not included second end **Casing Material:** Steel Wrenching Facility Type: Hexagon second end **Cross Section Size And Location:** 0.150 inches diameter first end and 0.153 inches diameter first end **Torsional Deflection Rating:** Not rated **Casing Surface Treatment:** Cadmium-plated finish **Casing Length Between Ferrules:**

Between 57.437 inches and 57.563 inches

Casing Outside Diameter:

0.688 inches

Casing Protective Device Type:

Rubber cover

NSN 6680-00-832-7566

Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided second end
Enddiameter:
1.813 inches first end
Lubrication Fitting:
Not provided second end
Corelength:
Between 58.547 inches and 58.859 inches
Core Rotation Direction:
Clockwise
Core Removability:
Nonremovable
Special Features:
Counterclockwise core rotation direction, torsion strength winding direction 15.0 pounds
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
T246-e