# NSN 6680-00-832-7566

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-832-7566

Thread Class:
2b second end
Thread Length:
0.375 inches second end
Overall Length:
Between 58.578 inches and 58.891 inches
Tip Length:
0.734 inches first end and 0.922 inches first end
Core Material:
Steel
Screw Thread Series Designator:
Uns first end
Core Surface Treatment:
Zinc coated
Core Diameter:
0.150 inches
Thread Location:
Internal second end
End Type:
Square male second end
Width Across Flats:
1.000 inches first end
End Connection Type:
Threaded internal second end
Setscrew:
Not included second end
Casing Material:
Steel
Wrenching Facility Type:
Hexagon second end
Cross Section Size And Location:
0.150 inches diameter first end and 0.153 inches diameter first end
Torsional Deflection Rating:
Not rated
Casing Surface Treatment:
Cadmium-plated finish
Casing Length Between Ferrules:
Between 57.437 inches and 57.563 inches
Casing Outside Diameter:
0.688 inches
Casing Protective Device Type:
Rubber cover

## NSN 6680-00-832-7566

Flexible Shaft Assembly - Page 2 of 2



Swivel End:

Not provided second end

#### Enddiameter:

1.813 inches first end

### **Lubrication Fitting:**

Not provided second end

### Corelength:

Between 58.547 inches and 58.859 inches

#### Core Rotation Direction:

Clockwise

Core Removability:

Nonremovable

#### **Special Features:**

Counterclockwise core rotation direction, torsion strength winding direction 15.0 pounds

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

T246-e