## NSN 6680-00-833-5686

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-833-5686 **Overall Length:** 15.375 inches Media For Which Designed: Lubricating oil **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.3/+3.0 **Outlet Connection Size:** 1/2 in. Npt Base: Not included Float Type: Guided

Float Material:

Steel

## NSN 6680-00-833-5686

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Solid rod
Integral Heat Source:
Not included
Maximum Working Pressure:
300.0 pounds per square inch
Inlet Connection Size:
1/2 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.3
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t