## NSN 6680-00-844-4806

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-844-4806

Body Material:
Iron, cast

**Body Material:** Iron, cast **Maximum Operating Pressure:** 150.0 pounds per square inch Media For Which Designed: Diesel fuel and jet fuels **Inlet Connection Type:** Drilled flange Inlet Bolt Hole Quantity: **Maximum Operating Temp:** 150.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 2.000 in. Npt **Measurement Unit:** Gallon Scale Measurement Range: +0.0/+9999.0 **Outlet Connection Type:** Drilled flange **Smallest Increment Indicated:** 0.01

Displacement Type:

Installation Location:

Any acceptable

Liquid Flow Rate:

100.0 gallons per minute

**Register Type:** 

Wheel

Rotor

**Reset Feature:** 

Provided

**Printing Mechanism:** 

Not provided

**Inlet Union Connection:** 

Not provided

**Outlet Connection Size:** 

2.0 in. Npt

**Outlet Bolt Hole Quantity:** 

## NSN 6680-00-844-4806

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



| Outlet Union Connection:                          |
|---|
| Not provided                                      |
| Reference Number Differentiating Characteristics: |
| With two 2 in. To 1-1/2 in. Threaded bushing      |
| Shelf Life:                                       |
| N/a   |
| Unit Of Measure:                                  |
|   |
| Demilitarization:                                 |
| No  |
| Fiig:   |

T134-d