

View Online at <https://aerobasegroup.com/nsn/6680-00-850-9334>

Thread Class:

2b second end

Thread Direction:

Right-hand second end

Overall Length:

Between 41.0781 inches and 41.3906 inches

Thread Depth:

0.375 inches second end

Tip Length:

0.950 inches second end and 1.010 inches second end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Zinc coated

Core Diameter:

0.150 inches

Thread Location:

Internal second end

End Type:

Square male second end

Width Across Flats:

1.000 inches first end

End Connection Type:

Threaded internal second end

Setscrew:

Not included second end

Casing Material:

Rubber and steel

Wrenching Facility Type:

Hexagon second end

Cross Section Size And Location:

0.150 inches diameter first end and 0.153 inches diameter first end

Casing Surface Treatment:

Any acceptable

Casing Length Between Ferrules:

Between 39.9375 inches and 40.063 inches

Casing Outside Diameter:

Between 0.300 inches and 0.500 inches

Casing Protective Device Type:

Plastic cover or rubber cover

Swivel End:

Not provided second end

Enddiameter:

1.187 inches first end

Lubrication Fitting:

Not provided second end

Corelength:

Between 41.0468 inches and 41.359 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Special Features:

Counterclockwise core rotation direction, torsion strength winding direction 15.0 pounds

Fsc Application Data:

Tachometer and speedometer vehicular a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e