

View Online at <https://aerobasegroup.com/nsn/6680-00-850-9334>

**Thread Class:**

2b second end

**Thread Direction:**

Right-hand second end

**Overall Length:**

Between 41.0781 inches and 41.3906 inches

**Thread Depth:**

0.375 inches second end

**Tip Length:**

0.950 inches second end and 1.010 inches second end

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns first end

**Core Surface Treatment:**

Zinc coated

**Core Diameter:**

0.150 inches

**Thread Location:**

Internal second end

**End Type:**

Square male second end

**Width Across Flats:**

1.000 inches first end

**End Connection Type:**

Threaded internal second end

**Setscrew:**

Not included second end

**Casing Material:**

Rubber and steel

**Wrenching Facility Type:**

Hexagon second end

**Cross Section Size And Location:**

0.150 inches diameter first end and 0.153 inches diameter first end

**Casing Surface Treatment:**

Any acceptable

**Casing Length Between Ferrules:**

Between 39.9375 inches and 40.063 inches

**Casing Outside Diameter:**

Between 0.300 inches and 0.500 inches

**Casing Protective Device Type:**

Plastic cover or rubber cover

**Swivel End:**

Not provided second end

**Enddiameter:**

1.187 inches first end

**Lubrication Fitting:**

Not provided second end

**Corelength:**

Between 41.0468 inches and 41.359 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Special Features:**

Counterclockwise core rotation direction, torsion strength winding direction 15.0 pounds

**Fsc Application Data:**

Tachometer and speedometer vehicular a

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T246-e