

View Online at <https://aerobasegroup.com/nsn/6680-00-851-4578>

Overall Length:

39.430 inches

Media For Which Designed:

Stoddard solvent

Inlet Connection Type:

Threaded

Integral Relief Valve:

Not included

Design Type:

Case

Unit Type:

Mounted

Scale Quantity:

3

Construction:

Inclosed w/sight window

Outlet Connection Type:

Threaded

Scale Marking:

Lb per hour; cc per min.

Scale Type:

Direct capacity reading

Float Quantity:

3

Tube Material:

Glass

Mounting Method:

Flush panel

Carrying Handle:

Not included

Dial Scale Marking Range:

+1.0/+400.0

Outlet Connection Size:

0.750 in. Od

Base:

Not included

Float Type:

Guided

Float Material:

Steel, corrosion resisting

Guide Type:

Beaded tube

Integral Heat Source:

Not included

Maximum Working Pressure:

250.0 pounds per square inch

Inlet Connection Size:

0.750 in. Od

Metering Tube Quantity:

3

Dial Scale Smallest Increment:

1/2 lb; 1/5 cc

Dial Scale Reference Pointer:

Not included

Float Quantity Per Tube:

1

Spinning Float:

Not included

Integral Pulsation Dampener:

Not included

Inlet Connection Position For Which Designed:

Horizontal

Inlet Connection Device Type:

Stationary

Outlet Connection Position For Which Designed:

Horizontal

Outlet Connection Device Type:

Stationary

Alarm Signal:

Not included

Reference Number Differentiating Characteristics:

Yas differentiated by replies to metering tube qty, tube material, scale qty, scale type, media for which designed, scale marking, dial scale marking range, dial scale smallest increment, w/scales calibrated for mil-f7024a, type 2, at 80 degrees f

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T134-t