

View Online at <https://aerobasegroup.com/nsn/6680-00-851-4578>

**Overall Length:**

39.430 inches

**Media For Which Designed:**

Stoddard solvent

**Inlet Connection Type:**

Threaded

**Integral Relief Valve:**

Not included

**Design Type:**

Case

**Unit Type:**

Mounted

**Scale Quantity:**

3

**Construction:**

Inclosed w/sight window

**Outlet Connection Type:**

Threaded

**Scale Marking:**

Lb per hour; cc per min.

**Scale Type:**

Direct capacity reading

**Float Quantity:**

3

**Tube Material:**

Glass

**Mounting Method:**

Flush panel

**Carrying Handle:**

Not included

**Dial Scale Marking Range:**

+1.0/+400.0

**Outlet Connection Size:**

0.750 in. Od

**Base:**

Not included

**Float Type:**

Guided

**Float Material:**

Steel, corrosion resisting

**Guide Type:**

Beaded tube

**Integral Heat Source:**

Not included

**Maximum Working Pressure:**

250.0 pounds per square inch

**Inlet Connection Size:**

0.750 in. Od

**Metering Tube Quantity:**

3

**Dial Scale Smallest Increment:**

1/2 lb; 1/5 cc

**Dial Scale Reference Pointer:**

Not included

**Float Quantity Per Tube:**

1

**Spinning Float:**

Not included

**Integral Pulsation Dampener:**

Not included

**Inlet Connection Position For Which Designed:**

Horizontal

**Inlet Connection Device Type:**

Stationary

**Outlet Connection Position For Which Designed:**

Horizontal

**Outlet Connection Device Type:**

Stationary

**Alarm Signal:**

Not included

**Reference Number Differentiating Characteristics:**

Yas differentiated by replies to metering tube qty, tube material, scale qty, scale type, media for which designed, scale marking, dial scale marking range, dial scale smallest increment, w/scales calibrated for mil-f7024a, type 2, at 80 degrees f

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T134-t