Rate Of Flow Transmitter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-854-6157

'	erminal Quantity:
4	
T	erminal Type:
F	Pin contacts
C	Overall Length:
2	2.500 inches
C	Overall Width:
1	.120 inches
C	Current Type:
A	AC
F	requency Rating:
E	Between 0.12 kilohertz and 1.2 kilohertz
A	Attachment Feature Quantity:
2	2
C	Overall Thickness:
3	3.000 inches
4	Actuation Method:
F	vivoted vane and magnet
١	/oltage Rating:
С	0.030 volts
E	Electrical Connection Quantity:
1	
E	Electrical Connection Controlling Agency:
^	Nn
E	Electrical Connection Identifying Number:
F	Part no. An3102a-10sl-4p
Ν	lechanical Connection Quantity:
2	<u>.</u>
Ν	lechanical Connection Size:
1	/2 in. Od
N	lechanical Connection Type:
F	lared tube
N	lounting Method:
T	hd male tube
N	leasurement Range:
+	-190.0/+1900.0 pounds per hour
F	Phase:
S	Single
	Reference Number Differentiating Characteristics:
	As differentiated by k factor 20 point calibration using mil-f-7024a,
	Shelf Life:

type 2 at 80 degrees f, form 127

N/a

## NSN 6680-00-854-6157

Rate Of Flow Transmitter - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

T145-b