Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-854-7951

	verall Length:
1	5.875 inches
M	edia For Which Designed:
L	ubricating oil
Ir	let Connection Type:
Т	hreaded
D	ial Range:
+	3.0/+30.0
lr	tegral Relief Valve:
N	ot included
D	esign Type:
С	ase
U	nit Type:
N	lounted
S	cale Quantity:
1	
С	onstruction:
S	ide plate
0	utlet Connection Type:
Т	hreaded
S	cale Marking:
С	c per min
S	cale Type:
D	irect capacity reading
F	loat Quantity:
1	
т	ube Material:
G	lass
N	lounting Method:
F	lush panel
С	arrying Handle:
N	ot included
D	ial Scale Marking Range:
+)	2.0/+35.0
0	utlet Connection Size:
1,	/8 in. lps
В	ase:
N	ot included
F	loat Type:
G	uided
_	loat Material:

NSN 6680-00-854-7951

Flow Rate Indicating Meter - Page 2 of 2



Guide Type: Beaded tube **Integral Heat Source:** Not included **Inlet Connection Size:** 1/8 in. lps Metering Tube Quantity: 1 **Dial Scale Smallest Increment:** 2 cc **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Stationary **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Stationary Alarm Signal: Not included **Reference Number Differentiating Characteristics:** Cpzf, awgj, apsj, ateq, ackl, astw, bhby, aewh, cpzj, cpzk Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T134-t