## NSN 6680-00-861-2964

Liquid Quantity Indicator Set - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-00-861-2964

Ac Voltage Rating: Between 105.0 volts and 125.0 volts Frequency Rating: Between 320.0 hertz and 480.0 hertz End Application: T-38 acft Electrical Connection Quantity: 2 Indicator Quantity: 1 Special Features: Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 11 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	view Online at https://aerobasegroup.com/hsh/ooou-ou-oo1-2964
Ac Voltage Rating: Between 105.0 volts and 125.0 volts Frequency Rating: Between 320.0 hertz and 480.0 hertz End Application: T-38 acft Electrical Connection Quantity: 2 Indicator Quantity: 1 Special Features: Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 1/l liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n 165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mill-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	Current Type:
Between 105.0 volts and 125.0 volts  Frequency Rating: Between 320.0 hertz and 480.0 hertz  End Application: T-38 acft  Electrical Connection Quantity: 2 Indicator Quantity: 1 Special Features: Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 1/4 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life: N/a Unit Of Measure:	Ac
Frequency Rating: Between 320.0 hertz and 480.0 hertz  End Application: T-38 acft  Electrical Connection Quantity: 2 Indicator Quantity: 1 Special Features: Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	Ac Voltage Rating:
Between 320.0 hertz and 480.0 hertz  End Application: T-38 acft  Electrical Connection Quantity: 2 Indicator Quantity: 1 Special Features: Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5  Ibs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10  Iliters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-1-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life: N/a  Unit Of Measure:	Between 105.0 volts and 125.0 volts
End Application: T-38 acft  Electrical Connection Quantity: 2  Indicator Quantity: 1  Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-1-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life: N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Flig:	Frequency Rating:
T-38 acft  Electrical Connection Quantity:  2  Indicator Quantity:  1  Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Between 320.0 hertz and 480.0 hertz
Electrical Connection Quantity:  2 Indicator Quantity:  1 Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 Ibs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Flig:	End Application:
Indicator Quantity:  1  Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 1/liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	T-38 acft
Indicator Quantity:  Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-1-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Electrical Connection Quantity:
Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	2
Special Features:  Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Indicator Quantity:
Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	1
master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:  ——  Demilitarization:  Yes - demil/mli  Fiig:	Special Features:
lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches fo
liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5
67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 1
connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	67-2058-1862 or equal; master connector p/n165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:	connector p/n 165-10; accuracy per mil-l-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	liters
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	<del></del>
Fiig:	Demilitarization:
	Yes - demil/mli
A534t0	Fiig:
	A534t0