## NSN 6680-00-865-9354

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-865-9354 Media For Which Designed: Liquid **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Indicator Type:** Float extension stem connected to dial pointer **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Armored **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Steel, stainless **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +1.5/+15.0 **Outlet Connection Size:** 1.000 in. Npt Base: Not included Float Type:

Guided Float Material: Steel, stainless

## NSN 6680-00-865-9354

Flow Rate Indicating Meter - Page 2 of 2



| Guide Type:  |
|--|
| Solid rod  |
| Integral Heat Source:  |
| Not included   |
| Inlet Connection Size:   |
| 1.000 in. Npt  |
| Metering Tube Quantity:  |
| 1  |
| Dial Scale Reference Pointer:  |
| Not included   |
| Spinning Float:  |
| Not included   |
| Integral Pulsation Dampener:   |
| Not included   |
| Inlet Connection Position For Which Designed:  |
| Horizontal   |
| Inlet Connection Device Type:  |
| Stationary   |
| Outlet Connection Position For Which Designed:   |
| Horizontal   |
| Outlet Connection Device Type:   |
| Stationary   |
| Alarm Signal:  |
| Not included   |
| Special Features:  |
| Left side scale for mil-h-5606 sp gr 0.805 at 180 degrees f, right side scale for mil-l-7808 sp gr 0.878 at 180 degrees f; serial no. 6503-78316 |
| Reference Number Differentiating Characteristics:  |
| As differentiated by special features  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Fiig:  |
| T134-t   |
|  |
|  |