

NSN 6680-00-878-2808 Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-878-2808 **Overall Length:** 39.430 inches Media For Which Designed: Aircraft fuel **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Lb per hr Scale Type: Direct capacity reading Float Quantity: 3 **Tube Material:** Glass

Mounting Method:

Flush panel

Carrying Handle:

Not included

Dial Scale Marking Range:

+315.0/+35000.0

Outlet Connection Size:

2 in. Tube od size

Base:

Not included

Float Type:

Guided

Float Material:

Steel, corrosion resisting

NSN 6680-00-878-2808

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
125.0 pounds per square inch
Inlet Connection Size:
2 in. Tube od size
Metering Tube Quantity:
2
Dial Scale Smallest Increment:
1lb
Dial Scale Reference Pointer:
Not included
Float Quantity Per Tube:
1
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk, abhp, acqw, cpzd, cpzp, cpzq, arth, bhcm, cpzr, and cpzs
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
T134-t