NSN 6680-00-878-2810

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-878-2810 **Overall Length:** 33.870 inches Media For Which Designed: Aircraft fuel **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Lb per hr Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +135.0/+740.0 **Outlet Connection Size:** 1/2 in. lps Base: Not included Float Type: Guided Float Material: Steel, corrosion resisting **Guide Type:**

Beaded tube

NSN 6680-00-878-2810

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source:
Not included
Maximum Working Pressure:
125.0 pounds per square inch
Inlet Connection Size:
1/2 in. lps
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
1/2 lb
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk, abhp, acqw, cpzd, cpzp, cpzq, arth, bhcm, cpzr, cpzs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t