NSN 6680-00-879-3877

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-879-3877



Overall Length: 33.870 inches Media For Which Designed: Stoddard solvent **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Lb per hr Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +1025.0/+53000.0 **Outlet Connection Size:** 3 in. Od tube Base: Not included Float Type: Guided Float Material: Steel, corrosion resisting **Guide Type:** Beaded tube

NSN 6680-00-879-3877

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source:
Not included
Maximum Working Pressure:
125.0 pounds per square inch
Inlet Connection Size:
3 in. Od tube
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
2-1/2 lb
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
As differentiated by rqmts no. 3 and 4
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t