Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-879-3878

Overall Length:		
33.870 inches		
Media For Which D	signed:	
Stoddard solvent		
Inlet Connection Ty)e:	
Threaded		
Integral Relief Valv		
Not included		
Design Type:		
Case		
Unit Type:		
Mounted		
Scale Quantity:		
1		
Construction:		
Inclosed w/sight wind		
Outlet Connection	ype:	
Threaded		
Scale Marking:		
Lb per hr		
Scale Type:		
Direct capacity readi	g	
Float Quantity:		
1		
Tube Material:		
Glass		
Mounting Method:		
Flush panel		
Carrying Handle:		
Not included		
Dial Scale Marking	lange:	
+170.0/+940.0		
Outlet Connection	ize:	
1/2 in. lps		
Base:		
Not included		
Float Type:		
Guided		
Float Material:		
Steel, corrosion resi	ting	
Guide Type:		

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source: Not included Maximum Working Pressure: 250.0 pounds per square inch **Inlet Connection Size:** 1/2 in. lps Metering Tube Quantity: 1 **Dial Scale Smallest Increment:** 1/2 lb **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Stationary **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Stationary Alarm Signal: Not included **Reference Number Differentiating Characteristics:** Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T134-t