Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-879-9305

•••	erall Length:
21.2	260 inches
Me	dia For Which Designed:
Lub	ricating oil
Inle	t Connection Type:
Thr	eaded
Dia	I Range:
+0.3	35/+4.50
Inte	gral Relief Valve:
Not	included
Des	sign Type:
Cas	se
Uni	t Type:
Мо	unted
Sca	le Quantity:
1	
Сог	nstruction:
Incl	osed w/sight window
Out	let Connection Type:
Thr	eaded
Sca	le Marking:
Gpr	n, lb per hr
Sca	le Туре:
Dire	ect capacity reading
Flo	at Quantity:
1	
Tuk	e Material:
Gla	ss
Мо	unting Method:
Flu	sh panel
Car	rying Handle:
Not	included
Dia	I Scale Marking Range:
+0.	5/+4.5
Out	let Connection Size:
3/4	in. Ips
Bas	se:
Not	included
Flo	at Type:
Gui	ded
	at Material:

NSN 6680-00-879-9305

Flow Rate Indicating Meter - Page 2 of 2



Guide Type: Beaded tube **Integral Heat Source:** Not included Maximum Working Pressure: 200.0 pounds per square inch **Inlet Connection Size:** 3/4 in. lps Metering Tube Quantity: 1 **Dial Scale Smallest Increment:** 0.05 gpm; 20 lb per hr **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Stationary **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Stationary Alarm Signal: Not included **Reference Number Differentiating Characteristics:** Cpzf, awgj, apsj, ateq, ackl, astw, bhby, aewh, cpzj, cpzk Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: T134-t