NSN 6680-00-879-9305

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-879-9305



Overall Length: 21.260 inches Media For Which Designed: Lubricating oil **Inlet Connection Type:** Threaded Dial Range: +0.35/+4.50 **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm, lb per hr Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.5/+4.5 **Outlet Connection Size:** 3/4 in. lps Base: Not included Float Type: Guided Float Material: Steel, corrosion resisting

NSN 6680-00-879-9305

Flow Rate Indicating Meter - Page 2 of 2



| Guide Type: |
|--|
| Beaded tube |
| Integral Heat Source: |
| Not included |
| Maximum Working Pressure: |
| 200.0 pounds per square inch |
| Inlet Connection Size: |
| 3/4 in. lps |
| Metering Tube Quantity: |
| 1 |
| Dial Scale Smallest Increment: |
| 0.05 gpm; 20 lb per hr |
| Dial Scale Reference Pointer: |
| Not included |
| Spinning Float: |
| Not included |
| Integral Pulsation Dampener: |
| Not included |
| Inlet Connection Position For Which Designed: |
| Horizontal |
| Inlet Connection Device Type: |
| Stationary |
| Outlet Connection Position For Which Designed: |
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Reference Number Differentiating Characteristics: |
| Cpzf, awgj, apsj, ateq, ackl, astw, bhby, aewh, cpzj, cpzk |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T134-t |