NSN 6680-00-882-7196

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-882-7196 **Overall Length:** 8.875 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **End Application:** Test stand no ot217-1 **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Cc per min Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0/+40.0 **Outlet Connection Size:** 0.125 in. Npt Base: Not included Float Type:

Guided

NSN 6680-00-882-7196

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel, corrosion resisting
Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
430.0 pounds per square inch
Inlet Connection Size:
0.125 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
1 cc
Dial Scale Reference Pointer:
Not included
Spinning Float:
Included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Swivel
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Ser no. 7412a1157a1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T13/Lt