Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-883-1021

• ••• ···
Overall Length:
5.500 inches
Media For Which Designed:
Hydraulic oil
Inlet Connection Type:
Threaded
End Application:
Lgm-30 minuteman missile
Integral Relief Valve:
Not included
Meter Type:
Float
Design Type:
Case
Unit Type:
Mounted
Scale Quantity:
2
Construction:
Side plate
Outlet Connection Type:
Threaded
Scale Marking:
Cu ft per hr
Scale Type:
Direct capacity reading
Float Quantity:
2
Tube Material:
Glass
Mounting Method:
Direct line
Carrying Handle:
Not included
Dial Scale Marking Range:
+10.0/+80.0
Outlet Connection Size:
0.125 in. Npt
Base:
Not included
Float Type:
Free
1100

Flow Rate Indicating Meter - Page 2 of 2



Float Material: Steel, corrosion resisting **Integral Heat Source:** Not included Maximum Working Pressure: 200.0 pounds per square inch Inlet Connection Size: 0.125 in. Npt **Metering Tube Quantity:** 2 **Dial Scale Smallest Increment:** 1 cu ft per hr **Dial Scale Reference Pointer:** Not included Float Quantity Per Tube: 1 **Spinning Float:** Not included Integral Pulsation Dampener: Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Swivel **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Swivel Alarm Signal: Not included **Reference Number Differentiating Characteristics:** As differentiated by serial no. 6807-48428 Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T134-t