

View Online at <https://aerobasegroup.com/nsn/6680-00-889-1538>

Overall Length:

39.430 inches

Media For Which Designed:

Calibration fluid

Inlet Connection Type:

Threaded

Integral Relief Valve:

Included

Design Type:

Case

Unit Type:

Mounted

Scale Quantity:

3

Construction:

Inclosed w/sight window

Outlet Connection Type:

Threaded

Scale Marking:

Phr

Scale Type:

Direct capacity reading

Float Quantity:

3

Tube Material:

Glass

Mounting Method:

Flush panel

Carrying Handle:

Not included

Unit Location:

Lower rear

Dial Scale Marking Range:

+3.5/+750.0

Outlet Connection Size:

3/4 in. Od tube

Base:

Not included

Float Type:

Guided

Float Material:

Steel, corrosion resisting

Guide Type:

Beaded tube

Integral Heat Source:

Not included

Maximum Working Pressure:

280.0 pounds per square inch

Inlet Connection Size:

3/4 in. Od tube

Metering Tube Quantity:

3

Dial Scale Smallest Increment:

0.05 phr

Dial Scale Reference Pointer:

Not included

Float Quantity Per Tube:

1

Spinning Float:

Not included

Integral Pulsation Dampener:

Not included

Inlet Connection Position For Which Designed:

Horizontal

Inlet Connection Device Type:

Stationary

Outlet Connection Position For Which Designed:

Horizontal

Outlet Connection Device Type:

Stationary

Alarm Signal:

Not included

Reference Number Differentiating Characteristics:

As differentiated by reply to rqmetsw/scales calibrated at 80 degrees f and additional checks at 70, 90 and 100 degrees f

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T134-t