Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-889-1539

| Overall Length:            |  |  |
|----------------------------|--|--|
| 39.430 inches              |  |  |
| Media For Which Designed:  |  |  |
| Calibration fluid          |  |  |
| Inlet Connection Type:     |  |  |
| Threaded                   |  |  |
| Integral Relief Valve:     |  |  |
| Included                   |  |  |
| Design Type:               |  |  |
| Case                       |  |  |
| Unit Type:                 |  |  |
| Mounted                    |  |  |
| Scale Quantity:            |  |  |
| 3                          |  |  |
| Construction:              |  |  |
| Inclosed w/sight window    |  |  |
| Outlet Connection Type:    |  |  |
| Threaded                   |  |  |
| Scale Marking:             |  |  |
| Phr                        |  |  |
| Scale Type:                |  |  |
| Direct capacity reading    |  |  |
| Float Quantity:            |  |  |
| 3                          |  |  |
| Tube Material:             |  |  |
| Glass                      |  |  |
| Mounting Method:           |  |  |
| Flush panel                |  |  |
| Carrying Handle:           |  |  |
| Not included               |  |  |
| Unit Location:             |  |  |
| Lower rear                 |  |  |
| Dial Scale Marking Range:  |  |  |
| +22.0/+4400.0              |  |  |
| Outlet Connection Size:    |  |  |
| 1-1/4 in. Od tube          |  |  |
| Base:                      |  |  |
| Not included               |  |  |
| Float Type:                |  |  |
| Guided                     |  |  |
| Float Material:            |  |  |
| Steel, corrosion resisting |  |  |
|                            |  |  |

## NSN 6680-00-889-1539

Flow Rate Indicating Meter - Page 2 of 2

| Guide Type:  |
|--|
| Beaded tube  |
| Integral Heat Source:  |
| Not included   |
| Maximum Working Pressure:  |
| 160.0 pounds per square inch   |
| Inlet Connection Size:   |
| 1-1/4 in. Od tube  |
| Metering Tube Quantity:  |
| 3  |
| Dial Scale Smallest Increment:   |
| 0.10 phr   |
| Dial Scale Reference Pointer:  |
| Not included   |
| Float Quantity Per Tube:   |
| 1  |
| Spinning Float:  |
| Not included   |
| Integral Pulsation Dampener:   |
| Not included   |
| Inlet Connection Position For Which Designed:  |
| Horizontal   |
| Inlet Connection Device Type:  |
| Stationary   |
| Outlet Connection Position For Which Designed:   |
| Horizontal   |
| Outlet Connection Device Type:   |
| Stationary   |
| Alarm Signal:  |
| Not included   |
| Reference Number Differentiating Characteristics:  |
| Yas differentiated by replies to meter tube qty, tube matl, scale qty, scale type, media for which designed, scale marking range, dial scale |
| smallest increment, w/scales calibrated at 80 degrees f w/additional temp checks at 70, 90 and 100 degrees f                                 |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| T134-t   |
|  |

AeroBase Group