## NSN 6680-00-913-2500



Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-913-2500 **Overall Length:** 9.625 inches Media For Which Designed: Nitrogen **Inlet Connection Type:** Threaded **End Application:** Brooks instrument div, emerson electric co, test stand, model no. Ttu155e **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Cc per min Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0/+125.0 **Outlet Connection Size:** 1/4 in. Npt Base: Not included

Float Type: Guided

## NSN 6680-00-913-2500

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Glass
Guide Type:
Hollow tapered rod
Integral Heat Source:
Not included
Maximum Working Pressure:
550.0 pounds per square inch
Inlet Connection Size:
1/4 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
12.5 cc per min
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t